

# LADDERS & SCAFFOLDING

## WHAT HEIGHT?

### STEPLADDER

Max. Height You Want to Reach*	Buy This Size
7'	4'
8'	5'
9'	6'
10'	7'
11'	8'
12'	10'
14'	12'
16'	14'
18'	16'
20'	18'
22', 24'	20'

\*Assumes a 5' 6" person with a vertical 12" reach.

### EXTENSION/STRAIGHT LADDERS

Height of Top Support Point	Buy This Size*
9' max.	16'
9' to 13'	20'
13' to 17'	24'
17' to 21'	28'
21' to 25'	32'
25' to 28'	36'
28' to 31'	40'

\*Reflects section overlap, ladder angle.

## WHAT LOAD CAPACITY?

### Formula:

Your Weight



Load Capacity

### Material Weight

Typically Add:  
**75 lbs.** For Heavy-Duty Projects  
**50 lbs.** For Light-Duty Projects



200 lbs.	CSA grade 3 Household
225 lbs.	CSA grade 2 Tradesman and Farm
250 lbs.	CSA grade 1 Construction and Industrial
300 lbs.	CSA grade 1A Construction and Industrial meets ANSI Type1A, Industrial Heavy Duty
375 lbs.	CSA grade 1AA Construction and Industrial meets ANSI Type1AA, Industrial Heavy Duty

## COMMERCIAL DUTY ALUMINUM STEPLADDERS (2400 SERIES)

CSA grade 2, ANSI type 2 – 225-lb. Load Rating

- Super tough molded copolymer utility top
- Durable yet light-weight extruded side rails
- 3" slip-resistant serrated steps
- Heavy-duty rubber safety shoes

MF064



### FEATHERLITE INDUSTRIAL LADDERS

Model No.	Nominal Height'	Open Height"	Highest Standing Height"	Base Width"	Base Depth"	Weight lbs.	Price /Each
MF063	4	45	24	18	31	9	
MF064	6	67	45	21	44	13	
MF065	8	90	67	23	56	19	
VC458	7	79	57	24	56	18	
VC459	10	114	92	28	69	26	



SAFETY PRODUCTS FOR INDUSTRY

## INDUSTRIAL EXTRA HEAVY-DUTY ALUMINUM STEPLADDERS (3400 SERIES)

CSA grade 1A, ANSI type 1A – 300-lb. load rating

High strength to weight ratio provides an economical alternative for general contract work

- Super tough copolymer top for strength and durability
- Wide 3" slip-resistant serrated aluminum steps for safe climbing
- Rugged outside zinc coated steel spreader arms
- 10" x 10" heavy-duty hinged utility tray for holding tools and paint accessories
- Heavy-duty slip-resistant safety shoes

VC241



### FEATHERLITE INDUSTRIAL LADDERS

Model No.	Nominal Height'	Open Height"	Highest Standing Point"	Base Width"	Base Depth"	Weight lbs.	Price /Each
VC241	4	46	23	18	30	11	
VC242	5	57-1/16	34-1/4	20-1/16	36-3/8	14	
VC243	6	68	45	21	43	16	
VC244	8	91	68	24	55	21	
VC245	10	114	91	27	68	27	
VC315	12	137	114	32	78	38	
VC316	14	160	137	34	94	60	
VC317	16	182	160	37	102	70	

## INDUSTRIAL HEAVY-DUTY ALUMINUM PLATFORM STEPLADDERS (3500 SERIES)

CSA grade 1A, ANSI type 1A – 300-lb. load rating

Ideal for general fixed height work

- Large comfortable slip-resistant platform, 14" x 18"
- Wide 3" slip-resistant serrated aluminum steps for safe climbing
- Outside J spreader arms
- Heavy-duty slip-resistant safety shoes

VC246



### FEATHERLITE INDUSTRIAL LADDERS

Model No.	Nominal Height'	Open Height"	Platform Height"	Base Width"	Base Depth"	Weight lbs.	Price /Each
MF069	4	46	23	21	28	13	
VC460	5	56	34	22	33	17	
VC246	6	68	46	24	42	19	
VC247	8	90	68	26	54	24	
VC248	10	114	92	29	66	30	
VC312	12	135	115	34	78	43	
VC313	14	157	136	36	87	52	
VC314	16	180	158	39	102	60	

## SAFETY DO'S

- Keep your body centered on the ladder. Hold the ladder with one hand while working with the other hand whenever possible. Never let your belt buckle pass beyond either ladder rail



- Move materials with extreme caution. Be careful pushing or pulling anything while on a ladder. You may lose your balance or tip the ladder

