

## ORBITAL JIG SAWS

- Keyless shoe adjustment with 45° in both directions and orbital action with four adjustment levels
- Quik-Lok™ blade change system and built-in dust collection port
- Tachometer feedback for constant cutting speed
- Includes: Dust shield and two blades

**Model No. TKZ868**  
**Mfg. No. 6268-21**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 6.5  
**Stroke Length:** 1"  
**Strokes per Minute (SPM):** 0-3000  
**Tool Weight:** 6.4 lbs.



**Milwaukee**

## SUPER SAWZALL®

- Maintains constant speed under load
- Variable speed trigger and dial speed control
- Quik-Lok™ blade clamp, tool-less blade change and impact protection
- Includes: Carrying case and one blade

**Model No. TLY299**  
**Mfg. No. 6538-21**  
**Price/Each \$**

### SPECIFICATIONS

**Stroke Length:** 1 1/4"  
**Amperage:** 15.0  
**Strokes per Minute:** 0-2800  
**Tool Weight:** 9.8 lbs.



**Milwaukee**

## JIG SAWS

- Uses tang style blades only
- Variable speed, vacuum port, three orbital settings plus straight cutting
- Adjustable base bevels from 0°-45° left and right
- Includes: One jig saw blade and carrying case

**Model No. TLY335**  
**Mfg. No. 4329K**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 3.9  
**Stroke Length:** 11/16"  
**Strokes per Minute (SPM):** 500-3100  
**Tool Weight:** 4.2 lbs.



**Makita**

## RECIPROCATING SAWS

- Powered by a 12 Amp motor with electronic speed control to maintain constant speed under load
- Variable speed trigger to match the speed of the saw to the application
- Durable body design that keeps dust and debris away from the motor, with rubber and felt seals to keep dust and water out for a longer tool life
- "Tool-less" blade change for fast blade installation and removal
- Engineered for demolition, metal cutting, wood cutting, drywall and plaster, plastics, and remodeling
- Tool hook secures the tool when not in use
- Well balanced design (only 7.3 lbs. and 17-5/8" long) for reduced operator fatigue and all-day use
- Large 2-finger trigger for added convenience
- Soft grip and handle for increased comfort
- Double insulated
- Includes: Reciprocating saw, 6" 6 TPI Wood-cutting saw blade, 6" 18 TPI Metal-cutting saw blade

**Model No. UAJ532**  
**Mfg. No. JR3051T**  
**Price/Each \$**

### SPECIFICATIONS

**Stroke Length:** 1-3/16"  
**Strokes per Minute (SPM):** 0-3000  
**Amps:** 12 A  
**Overall Length:** 17-5/8"  
**Net Weight:** 7.3 lbs.  
**Max. Cutting Capacity:** 5-1/8" Pipe & 10" Wood



**Makita**

## DEEP CUT BAND SAWS

- Variable speeds dial and trigger and 2-finger variable speed trigger
- Adjustable material guide
- Rear blade guard - 30% thicker steel protects the guard from bending or pinching during material break-through
- Includes: Carrying case

**Model No. TLV447**  
**Mfg. No. 6232-21**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 10.5  
**Saw Surface Feet per Minute (SFPM):** 0-420  
**Max Capacity**  
**Rectangular:** 4 7/8" x 4 7/8"  
**Round:** 4 7/8"  
**Tool Weight:** 17.5 lbs.



**Milwaukee**

## DEEP CUT PORTA-BAND® SAWS

- Dual bearing blade guide rollers increase durability in the blade support system
- Speed control knob allows to tailor the blade speed
- Blade tracking adjustment increases blade life
- Includes: Hex wrench and standard blade

**Model No. TKZ842**  
**Mfg. No. DWM120K**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 10.0  
**Saw Surface Feet per Minute (SFPM):** 100-350  
**Max Capacity**  
**Rectangular:** 5" x 4 3/4"  
**Round:** 5"  
**Tool Weight:** 14 lbs.



**DEWALT**

## ANTI-VIBRATION RECIPROCATING SAWS

- Features anti-vibration technology (AVT)
- Orbital change lever offers three stages and one straight cutting action
- Accepts standard 1/2" shank blades
- Includes: One saw blade and carrying case

**Model No. TGX675**  
**Mfg. No. JR3070CT**  
**Price/Each \$**

### SPECIFICATIONS

**Stroke Length:** 1 1/4"  
**Amperage:** 15.0  
**Strokes per Minute:** 0-2800  
**Tool Weight:** 9.5 lbs.



**Makita**

## SAWZALL® RECIPROCATING SAWS

- Powerful 12 Amp motor: Delivers 0-3000 SPM for high performance cutting in a variety of materials
- 1 1/8" stroke length
- Counter weighted mechanism: Provides reduced vibration for smoother operation
- Quik-Lok™ blade clamp for fast, tool-less blade changes
- Includes: Carrying case

**Model No. TLV201**  
**Mfg. No. 6519-31**  
**Price/Each \$**

### SPECIFICATIONS

**Stroke Length:** 1 1/8"  
**Amperage:** 12.0  
**Strokes per Minute:** 0-3000  
**Tool Weight:** 7.1 lbs.



**Milwaukee**